



ET-D3LEW200 (for 3-Chip DLP™ Projectors)

The Zero Offset Ultra Short Throw Fixed-Focus Lens is designed for compatibility with RZ21 series, RZ31 series projectors.

ET-D3LEW200 (for
3-Chip DLP™
Projectors)

<https://latam.connect.panasonic.com/pe/es/et-d3lew200for-3-chip-dlptm-projectors>

| | |
|--|--|
| Lens type | Short-Throw Zoom Lens |
| F-number | 2.5 |
| Focal length (f) | 13.8-18.1 mm (17/32"-23/32") |
| Screen size | 200-600 inches |
| Throw ratio -> 4K+ | 0.693 ~ 0.913:1 |
| Throw ratio -> WUXGA | 0.645 ~ 0.850:1 |
| Throw ratio -> SXGA+ | 0.699 ~ 0.921:1 |
| Auto Lens Identification function | PT-RQ32K/RZ31K/RS30K/RQ25K/RZ24K/RQ18K/RZ17K/RZ14K/RQ22K/RZ21K/RS20K |
| Compatible models | |
| Lens-shift -> Vertical | ±56 % |
| Lens-shift -> Horizontal | ±19 % |
| Zoom | Yes |
| Dimensions -> (W) | 250 mm(9 27/32") |
| Dimensions -> (H) | 193 mm(7 19/32") |
| Dimensions -> (D) | 495 mm(19 1/2") |
| Weight | Approx. 9.0 kg (19.8 lbs) |
| Applicable projectors | RQ35K Series/RQ32K/RZ31K Series/RQ25K Series/RQ22K/RZ21K Series/RZ16K/RZ14K |
| Dimensions(WxHxD) | 250 × 193 × 495 mm (9-27/32 × 7-19/32 × 19-1/2") |
| Footnote Description | * Value is for ceiling installations using the PT-RQ22K. Lens-shift value will vary by model. Please see the Throw Distance Calculator for more information. For floor installations, up and right shift will be defined as a positive value. Down and left shift will be defined as a negative value. |