



1/5-type rack size remote operation panel which supports PoE and IP control

AK-HRP1015

Remote Operation Panel 1/5-type rack size remote operation panel which supports PoE and IP control *Product Availability may vary depending on country

Key Features

1/5-type rack size remote operation panel

Colour LCD display allows GUI operation, and also supports PoE* and IP control

Camera serial control and IP control (RJ45 LAN cable) are supported.

Can be used for remote control of Panasonic studio camera, camera recorders, convertible cameras, and HD integrated cameras.

Functions for studio camera scene file store and load.

SD memory card slot for saving user files, scene file and updating firmware versions.

The robust LAN connector.



AK-HRP1015

<https://latam.connect.panasonic.com/pe/es/productos/broadcast-y-proav/ak-hrp1015>

| | |
|---|--|
| General -> Power Supply | 12 V DC (Power supply from camera: 10 V - 16 V DC) 42 V - 57 V DC (PoE power supply) |
| General -> Power Consumption | 0.44 A (Power supply from camera: 10 V - 16 V DC) 0.11 A (PoE power supply) |
| General -> Operating Temperature | 0 °C to 40 °C (32 °F to 104 °F) |
| General -> Operating Humidity | 90 % or less |
| General -> Storage Temperature | -20 °C to 60 °C (-4 °F to 140 °F) |
| General -> Weight | Approx. 1.5 kg (3.3 lb) |
| General -> Dimensions | W 82 mm x H 355 mm x D 124.4 mm (3-1/4 inches x 14 inches x 4-7/8 inches) |
| General -> Camera/CCU Control | Control signals (camera, CCU control) Power supply 16 V DC (when CCU connected) *1, 12 V DC (when camera connected) *1 |
| General -> Maximum Cable Length | When camera connected: 20 m (65.7 ft) When CCU connected: 50 m (164 ft) |
| Input/Output -> CCU connector | 10-pin, male x 1 |
| Input/Output -> PREVIEW connector | 9-pin, female x 1 |
| Input/Output -> LAN connector | RJ-45 x 1 (equipped with a robust LAN terminal connector) |
| Footnote Description | Can be provided from CCU. |