



Ofrezca más por menos con el proyector DLP™ 4K de 3 chips más pequeño y ligero del mundo de 16.000 lm

PT-RQ18K

Ofrezca más por menos con el proyector DLP™ 4K de 3 chips más pequeño y ligero del mundo de 16.000 lm

Key Features

El factor de forma compacto agiliza el flujo de trabajo

Crea una experiencia visual atractiva

Libre de mantenimiento para tu tranquilidad

Proyector láser DLP™ 4K de 3 chips con unidad de píxeles cuádruples

Brillo de 16.000 lúmenes





PT-RQ18K

<https://latam.connect.panasonic.com/pe/es/products/projectors/pt-rq18k>

Projector type	3-Chip DLP™ projector
DLP™ chip Panel size (mm)	20.3 mm (0.8 in) diagonal (16:10 aspect ratio)
DLP™ chip Panel size (inch)	20.3 mm (0.8 in) diagonal (16:10 aspect ratio)
DLP™ chip Number of Pixels	2,304,000 (1920 x 1200 pixels) x 3
Light Source	Laser diode
Light Output*1 *2	16,000 lm / 16,800 lm (Center) *3
Time until light output declines to 50 %*4	20,000 hours (NORMAL/QUIET), 24,000 hours (ECO)
Resolución	4K (3840 x 2400 pixels) (Quad Pixel Drive: ON)
Contrast Ratio*2	25,000:1 (Full On/Full Off, Dynamic Contrast [3])
Screen size (diagonal) (mm)	1.78–25.40 m (70–1000 in), 1.78–15.24 m (70–600 in) with ET-D75LE8/ ET-D3LET80, 3.05–15.24 m (120–600 in) with ET-D75LE95, 5.08–15.24 m (200–600 in) with ET-D3LEU100/D3LEW200
Screen size (diagonal) (inch)	1.78–25.40 m (70–1000 in), 1.78–15.24 m (70–600 in) with ET-D75LE8/ ET-D3LET80, 3.05–15.24 m (120–600 in) with ET-D75LE95, 5.08–15.24 m (200–600 in) with ET-D3LEU100/D3LEW200
Center-to-corner zone ratio*2	90 %
Lens	Optional (no lens included with this model)
Lens shift Vertical(From the origin point of the lens mounter)	±66 % (±52 % with ET-D75LE6/ET-D3LEW60, +71 % / +93 % with ET-D75LE95, ±66 % with ET-D3LEU100, ±57 % with ET-D3LEW200) (powered)
Lens shift Horizontal(From the origin point of the lens mounter)	±24 % (±18 % with ET-D75LE6/ET-D3LEW60, ±14 % with ET-D75LE95, -25 % / +30 % with ET-D3LEU100, ±18 % with ET-D3LEW200) (powered)
Keystone Correction Range	Vertical: ±45 ° (± 40 ° with ET-D75LE10/ET-D3LEW10/ET-D75LE20/ET-D3LES20, ±28 ° with ET-D75LE6/ET-D3LEW60, ±22 ° with ET-D3LEW50, ±15 ° with ET-D3LEW200, ±8 ° with ET-D3LEU100, +5 ° with ET-D75LE95), Horizontal: ±40 ° (±15 ° with ET-D3LEW50/ET-D75LE6/ET-D3LEW60, ±5 ° with ET-D3LEU100/ET-D3LEW200, 0 ° with ET-D75LE95) When [VERTICAL KEYSTONE] and [HORIZONTAL KEYSTONE] are used simultaneously, correction cannot be made exceeding a total of 55 °.
Terminals HDMI In	HDMI x 2 (Deep Color, compatible with HDCP 2.3, 4K/60p signal input**5)
Terminals DisplayPort	DisplayPort™ x 1 (Deep Color, compatible with HDCP 2.3, 4K/60p signal input**5)
Terminals Multi Projector Sync In	BNC x 1
Terminals Multi Projector Sync Out	BNC x 1
Terminals MULTI PROJECTOR SYNC IN/ 3D SYNC 1 IN/OUT(dual purpose)	-
Terminals MULTI PROJECTOR SYNC OUT/ 3D SYNC 2 OUT(dual purpose)	-
Terminals Serial In	D-sub 9-pin (female) x 1 for external control (RS-232C compliant)
Terminals Serial Out	D-sub 9-pin (male) x 1 for link control (RS-232C compliant)
Terminals REMOTE 1 IN	M3 stereo mini-jack x 1 for wired remote control
Terminals REMOTE 1 OUT	M3 stereo mini-jack x 1 for link control (for wired remote control)
Terminals Remote 2 In	D-sub 9-pin (female) x 1 for external control (parallel)
Terminals LAN	RJ-45 x 1 for network connection, PLink™ (Class 2) compatible, 10Base-T/100Base-TX, Art-Net compatible
Terminals USB	USB connector (Type A) x 1 for optional AJ-WM50 Series Wireless Module/USB memory
Terminals DC Out	USB Type A x 1 (for power supply, DC 5 V, 2 A)
Terminals Expansion Slot	Open slot for for function boards, Intel® SDM compatible
Power Supply	AC 100 V–120 V / AC 200 V–240 V, 50 Hz/60 Hz (The maximum value of light output is limited to 15,000 lm or less when using the projector with AC 100 V to AC 120 V. Other limitations apply*6.)
Power consumption Maximum power consumption	AC 200 V–AC 240 V : 1,190 W (1,220 VA) AC 100 V–AC 120 V : 1,080 W (1,090 VA)
Power consumption On-mode power consumption (Operating mode)[Normal]	1,030 W
Power consumption On-mode power consumption (Operating mode)[Eco]	820 W
Power consumption On-mode power consumption (Operating mode)[Quiet]	810 W
Operation Noise*2	43 dB (NORMAL/ECO), 40 dB (QUIET)
Dimensiones (AnxAlxP)	Approx. 550 x 220 x 570 mm (21 5/8" x 8 11/16" x 22 7/16") (not including protruding parts)
Weight*8	Approx. 35 kg (77.2 lbs)

Operating Environment	Operating temperature: 0–45 °C (32–113 °F*9), operating humidity: 10–80 % (no condensation)
Applicable software/application	Logo Transfer Software, Multi Monitoring & Control Software, Projector Network Setup Software, Early Warning Software, Geometry Manager Pro, Smart Projector Control for iOS/Android™
Note	<p>*1 This is the value when the Zoom Lens (Model No.: ET-D3LES20) is used with power supply voltage of AC 200 V to AC 240 V. The value varies depending on the lens.</p> <p>*2 Measurement, measuring conditions, and method of notation all comply with ISO/IEC 21118: 2020 international standards.</p> <p>*3 Average light-output value of all shipped products measured at center of screen in NORMAL Mode.</p> <p>*4 Around this time, light output will have decreased by approximately 50 %. IEC62087: 2008 Broadcast contents, NORMAL Mode, Dynamic Contrast [3], under conditions with 35 °C (95 °F), 700 m (2,297 ft) above sea level, and 0.15 mg/m³ of particulate matter. Estimated time until light output decreases to 50 % will vary depending on environment.</p> <p>*5 4K signals are converted to WUXGA (1920 x 1200 pixels) only for the PT-RZ24K and PT-RZ17K.</p> <p>*6 Maximum value of light output is further decreased in the following cases: when a function board is installed in the slot, when the light source is deteriorating from use, or when there is dust on the optical parts.</p> <p>*7 Measurement, measuring conditions, and method of notation all comply with ISO/IEC 21118: 2020 international standards. On-mode power consumption measured at 25 °C (77 °F) operating temperature at an altitude of 700 m (2,297 ft).</p> <p>*8 Average value. May differ depending on the actual unit.</p> <p>*9 When optional AJ-WM50 Series wireless module is attached, operating temperature range becomes 0–40 °C (32–104 °F). The operating environment temperature should be between 0 °C (32 °F) and 40 °C (104 °F) if the projector is used at an altitude between 1,400 m (4,593 ft) and 4,200 m (13,780 ft).</p>