



O sistema de soldagem a arco TAWERS-WG4 é adequado para aplicações de soldagem de CO<sub>2</sub>, MAG, MIG e aço inoxidável.

## TAWERS WG4 Arc welding system

### Key Features

Experiência de soldagem altamente precisa e eficiente

Mais fácil de usar com painel de toque e tela 3D

Para fabricação onde tudo está conectado

Cabos dispostos na parte traseira para economizar espaço



TAWERS WG4 Arc  
welding system

<https://latam.connect.panasonic.com/pe/pt/produtos/welding-machines/tawers-wg4-arc-welding-system>

|                           |                                                                                                                                                                |
|---------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Memory Capacity           | 40,000 points                                                                                                                                                  |
| Position Control Method   | Software Servo System                                                                                                                                          |
| External Memory I/F       | TP: SD memory card slot x 1 USB2.0 (Hi-speed supported) x2                                                                                                     |
| Number of control axes    | Simultaneous 6 axes (max. 27 axes)                                                                                                                             |
| Other Input/Output Signal | Dedicated Signal: Input 6 points, Output 8 pointsGeneral purpose signal: Input 40 points, Output 40 pointsSafety Input/Output: Input 8 points, Output 8 points |
| Input Power Supply        | 3-phase, AC200 V (+-10%), 50 Hz/60 Hz (+-2%)                                                                                                                   |
| Input Cable               | 14 mm2 (AWG6) or more                                                                                                                                          |
| Ground Cable              | 14 mm2 (AWG6) or more                                                                                                                                          |
| Applicable Welding Method | CO2/MAG/Stainless Steel MIGPulse MAG/Stainless Steel pulse MIG                                                                                                 |
| Output Current            | 30 A-350 A DC                                                                                                                                                  |
| Output Voltage            | 12 V-36 V DC                                                                                                                                                   |
| Rated Duty Cycle          | 10 Minute CycleCO2/MAG/Stainless Steel MIG: 80% Pulse MAG/Stainless Steel pulse MIG:60 %                                                                       |