

SOLID SHINE Series



3-Chip DLP™ Laser light source models
Lens not included with 3-Chip DLP™ models.



PT-RQ50K 50,000 lm Native 4K¹
51,000 lm (Center)



PT-RQ35K 30,500 lm 4K²
32,000 lm (Center)

PT-RZ34K 30,500 lm WUXGA³
32,000 lm (Center)



PT-RQ25K 20,000 lm 4K²
21,000 lm (Center)

PT-RZ24K 20,000 lm WUXGA³
21,000 lm (Center)

PT-RQ18K 16,000 lm 4K²
16,800 lm (Center)

PT-RZ17K 16,000 lm WUXGA³
16,800 lm (Center)



1-Chip DLP™ Laser light source models
Lens not included with 'L' models.



PT-REQ15/L 15,000 lm 4K²
15,500 lm (Center)

PT-REQ12/L* 12,000 lm 4K²
12,400 lm (Center)

PT-REQ10/L* 10,000 lm 4K²
10,300 lm (Center)

PT-REQ80/L* 8,000 lm 4K²
8,200 lm (Center)



PT-REZ15/L 15,000 lm WUXGA³
15,500 lm (Center)

PT-REZ12/L* 12,000 lm WUXGA³
12,400 lm (Center)

PT-REZ10/L* 10,000 lm WUXGA³
10,300 lm (Center)

PT-REZ80/L* 8,000 lm WUXGA³
8,200 lm (Center)

Large-Venue

Installation

Portable



1-Chip DLP™ Laser light source models
Lens not included with 'L' models.

NEW



PT-RQ7L 7,500 lm 4K⁴

PT-RQ6L 6,500 lm 4K⁴

Available from CY2024 Q4

PT-RZ7L* 7,500 lm WUXGA³

PT-RZ6L* 6,500 lm WUXGA³



PT-RZ790/L 7,000 lm WUXGA³
7,200 lm (Center)

PT-RZ690/L 6,000 lm WUXGA³
6,200 lm (Center)



1-Chip DLP™ Laser light source models (Lens fixed)



PT-FRQ60 6,000 lm 4K⁴
6,200 lm (Center)

PT-FRQ50 5,200 lm 4K⁴
5,400 lm (Center)



PT-FRZ60 6,000 lm WUXGA³
6,200 lm (Center)

PT-FRZ50 5,200 lm WUXGA³
5,400 lm (Center)



Short Throw model
PT-FRZ55⁶ 5,000 lm WUXGA³
5,200 lm (Center)



LCD Laser light source models



PT-MZ20KL 20,000 lm WUXGA³

PT-MZ17KL 16,500 lm WUXGA³

PT-MZ14KL 14,000 lm WUXGA³

PT-MZ11KL 11,000 lm WUXGA³

Installation

Short Throw

Peripheral

LCD Lamp based models



Featured image: PT-TW381R

PT-TW381R 3,300 lm WXGA

PT-TW380 3,300 lm WXGA

PT-TX440⁶ 3,800 lm XGA

PT-TX350⁶ 3,200 lm XGA

Media Processor



NEW

ET-FMP50

ET-SBFMP10 Function board type

Available from CY2024 Q4

Installation

Portable

Short Throw

Ultra Short Throw



LCD Laser light source models



PT-MZ882 8,200 lm WUXGA

PT-MZ782 7,500 lm WUXGA

PT-MZ682 6,500 lm WUXGA



LCD Laser light source models (Lens fixed)



PT-VMZ71* 7,000 lm WUXGA

PT-VMZ61* 6,200 lm WUXGA

PT-VMZ51 5,200 lm WUXGA

PT-VMZ51S 5,200 lm WUXGA



PT-LMZ460 4,600 lm WUXGA

PT-LMZ420 4,200 lm WUXGA

PT-LMW460 4,600 lm WXGA

PT-LMW420 4,200 lm WXGA

PT-LMX460 4,600 lm XGA

PT-LMX420 4,200 lm XGA



LCD Laser light source models (Lens fixed)



PT-TMZ400 4,000 lm WUXGA

PT-TMW380 3,800 lm WXGA

PT-TMX380 3,800 lm XGA



LCD Laser light source models (Lens fixed)



PT-CMZ50 5,200 lm WUXGA

LCD Lamp based models



PT-VV360 4,000 lm WXGA



PT-VX430 4,500 lm XGA



PT-LW376 3,600 lm WXGA



PT-LW336 3,100 lm WXGA



PT-LB426 4,100 lm XGA



PT-LB386 3,800 lm XGA



PT-LB356 3,300 lm XGA

PT-LB306³ 3,100 lm XGA

1: Resolution 4096 x 2160 Pixels. 2: Resolution 3840 x 2400 Pixels (Quad Pixel Drive: ON).
3: Available in Japan, US and Canada 4: Resolution 3840 x 2160 Pixels (With Quad Pixel Drive).
5: HDMI/DIGITAL LINK input only. 6: The availability varies depending on the country.
7: HDMI/DIGITAL LINK input only. Supports signals up to 4K/30p.
8: To operate wireless projection, the optional Wireless Module AJ-WM50 is required.
9: HDMI input only. Supports signals up to 4K/30p.
10: To operate wireless projection, the optional Wireless Module ET-WML100 (Stock limited)/AJ-WM50 is required.

*: Available in black/white cabinet.
S: The projector is able to emulate the same control commands of most previous Panasonic projectors when it is replacing.

Note: [L] Lens-less model. The specifications are subject to change without notice.
For more information, please visit the website >> <https://docs.connect.panasonic.com/projector/>